

ARRI ^{ARRI}
SOFTLIGHT



ARRI SOFTLIGHT

The ARRI Tungsten Softlights, with their unique optical design and rugged construction, complement the ARRI Spotlight range, particularly for studio use but also on location where large area softlights are required. Light is emitted from virtually the entire frontal rectangular area and, as a result, the units can be positioned close together to provide larger area multiple arrays of softlights as and when required.

The reflectors are coated with a specially formulated heat resistant paint which refuses to discolour - original units are unchanged after many years of use!

More importantly, there is no colour temperature shift from these matt finished indirect reflectors - whether old or new.

The egg crate, hinged and removable for bulb replacement, is an integral part of the optical design and provides considerable beam-edge control.

Each bulb is separately protected by an over-current sensor device. Automatic trip circuit breakers are used on the manual softlights and re-settable push-button breakers on the pole operated units.

Slot-in removable colour frames are fitted on both 5kW and 2.5kW softlights.

These are true large area softlights for the discerning professional lighting director.

- 5kW or 2.5kW manual or pole-operated
- Large area
- Even illumination
- Life long reflectors
- Egg crate beam edge control
- Quick change colour frames
- Electrically protected bulbs



SOFTLIGHT 5000W

Manual
2.5/5kW - 220/240V L1.76580.E


Size (mm): 830H x 720W x 275L
Weight (kg): 29

Pole Operated
2.5/5kW - 220/240V L1.76590.IK


Physical
Size (mm): 830H x 720W x 305L
Weight (kg): 29

Bulb (x 4): P2/10 625W
P2/7 1000W
P2/12 1250W

Light Output (lux)* at 5kW:



Light Output (Foot candles)



Egg Crate
L2.76586.0




Colour Frame
L2.76588.0

Combo Stand
LA.1010.A

Lightweight Single
Lift Wind Up Stand
LS.6



Operating Pole
0.95m - 2.5m LS.428 - 2.5
1.40m - 4.0m LS.428 - 4.0



SOFTLIGHT 2500W

Manual
1250/2.5KW - 220/240V L1.76780.B


Size (mm): 485H x 720W x 275L
Weight (kg): 20

Pole Operated
1250/2.5kW - 220/240V L1.76780.IK


Physical
Size (mm): 485H x 720W x 305L
Weight (kg): 20

Bulb (x 2): P2/10 625W
P2/7 1000W
P2/12 1250W

Light Output (lux)* at 2.5kW:



Light Output (Foot candles)




Egg Crate and Diffuser Frame
L4.76591.0



Combo Stand
LA.1010.A



Operating Pole
0.95m - 2.5m LS.428 - 2.5
1.40m - 4.0m LS.428 - 4.0



*1000 lux gives correct exposure for 200ASA film with aperture f4 at 24fps
In order to maintain the highest possible standards, ARRI (GB) Ltd reserves the right to alter specifications without notice